

D6500 打印光机

Display technique	0.65" inch DMD
Resolution	1920*1080
Light source	UV405 LED/UV385LED
Light channel	Singe channel
Brightness	2.5W @50W; 3.0W@70W;
Focus	19 to 23
Contrast	1500 : 1
Uniformity	>90%
Distortion	<0.12%
Pixel size	96x54@0.05mm, 160x90@0.083mm
Offset	Without offset
Power supply	DC 12V/5A
Total power	<60W
Dimension	L210*W120*H130 (mm) L210*W158*H130 (mm)[含镜头]
Material	Body: All metal; Optics: All glass;
Input interface	HDMI x1
	Mini USB x1
Software	Power Soft switch,LED onoff,LED Exposure Current Adjust
	Image Short-Axis and Long-Axis Image Flip
	Windows/Linux 32,64-bit OS platform SDK support
	Custom Logo, and Other requirements

Image size VS Distance (mm)

Resolution	Image size		Distance	
	W	H	Min	Max
0.05	96	54	96	122
0.06	115	65	122	155
0.07	134	76	149	187
0.08	154	86	175	220
0.09	160	90	188	230







此款光机是变焦镜头，最佳打印尺寸 96X54 到 144X81，打印距离 96-200，打印精度 50-80（微米）。



刘利 liuli
DLP 系列产品销售工程师

上海意仪电子科技有限公司

shanghaiyiyidianzikejiyouxiangongsi



15618587576/15921998772



15618587576@163.com



021-64642232



021-64642232



上海市徐汇区漕宝路 36 号和诚
商务大厦 2 号楼 408 室



3D 扫描 3D 在线检测 3D 打印 光刻 AOI 自动光学检测 SPI 锡膏检测 PIN 背板检测 IC 引脚翘曲共面检测 锂电池检测 手机零部件检测等



<http://www.yiyill.icoc.me/>