

TYPE	SAME DIMENSIONS AS YUASA TYPE	CAPACITY (Ah) 10HR	DIMENSION (±2MM)			WEIGHT (KG)	REGULAR CHARGE CURREN T (A)	ASSEMBLY FIGURE	TERMINAL TYPE	CCA @-18°C
			L	W	H					
(6 VOLT)										
YS6-4-2A	6N4-2A	4	71	71	94	0.84	0.40		-	25
YS6-6-3B	6N6-3B	6	98	56	116	1.33	0.60		5	50
YS6N11A-3A	6N11A-3A	11	119	59	128	1.85	1.10		5	100
YS6N11A-1B	6N11A-1B	11	119	59	128	1.84	1.10		5	100
YS6-12B	3-MA-12	12	105	77	140	2.05	1.20		5	90
(12 VOLT)										
YS12-2.5L-C	YB2.5L-C	2.5	80	70	105	1.02	0.25		-	25
YS12-3L-A	YB3L-A/YB3L-B	3	98	56	109	1.23	0.30		5	30
YS12-4L-B	YB4L-B	4	120	71	91	1.64	0.40		4	50
YS12-4HL-B	YB4L-B	5	120	71	91	1.69	0.50		4	50
YS12-5-C		5	152	50	106	1.86	0.50		22	65
YS12-5L-B	YB5L-B	5	120	60	128	1.80	0.50		22	65
YS12-5.5-4B	12N5.5-4A	6.5	135	60	130	2.31	0.65		4	70
YS12-5.5-3B	12N5.5-3A/12N5.5-3B	6.5	135	60	130	2.31	0.65		4	70
YS12-6.5	YTX6.5-BS	7	139	66	101	2.26	0.65		5	70
YS12-6.5L	12N6.5-3B	6.5	139	66	101	2.26	0.65		5	70
YS12-7A-3A	12N7A-3A/YB7BL-B	7	149	59	130	2.57	0.70		5	95
YS12-7A-4A	12N7A-4A/YB7B-B	7	149	59	130	2.57	0.70		5	95
YS12-7B-B2	YB7A-A2	7	149	60	130	2.43	0.70		4	80
YS12-7C-A	YB7C-A	8	129	89	114	2.89	0.80		1	80
YS12-7-A	YB7-A/B, 12N7-4A/B	8	135	75	133	2.82	0.80		5	95
YS12-7L-A	YB7L-A	8	135	75	133	2.82	0.80		5	95
YS12-9L-B	12N9-3B/YB9L-B	9	135	75	139	2.82	0.80		5	95
YS12-9-B	12N9-4B-1/YB9-B	9	135	75	139	3.03	0.90		5	105
YS12-10L-A2	YB10L-A2/YB10L-B2	11	134	88	145	3.95	1.10		9	140
YS12-10A-A2	YB10A-A2	11	134	88	155	4.06	1.10		9	140
YS12-12AL-A	YB12AL-A	12	134	80	161	4.35	1.20		5	120
YS12-12A-A	12N12A-4A-1,YB12A-A	12	134	80	161	4.35	1.20		5	120
YS12-12A-A2	YB12A-A2	12	134	80	161	4.20	1.20		4	140
YS12-12AL-A2	YB12AL-A2	12	134	80	161	4.20	1.20		4	140
YS12-14-A2	YB14-A2	14	134	88	166	4.84	1.40		9	190
YS12-14L-A2	YB14L-A2	14	134	88	166	4.84	1.40		9	190
YS12-14A-A1	YB14A-A1	13	135	89	170	4.44	1.30		5	160
YS12-14A-A2	YB14A-A2	14	134	88	176	5.01	1.40		9	170
YS12-14AL-A2	YB14AL-A2	14	134	88	176	5.01	1.40		9	170
YS12-16AL-A2	YB16AL-A2	16	205	70	162	5.79	1.60		6	160
YS12-16A-AB	HYB16A-AB	16	150	90	180	4.98	1.60		6	120
YS51913 ^Δ	51913	21	183	79	171	6.04	2.10		3	210
YS12-N18-A	Y50-N18-A	20	205	87	162	7.39	2.00		6	230
YS12-N18L-A	Y50-N18L-A	20	205	87	162	7.39	2.00		6	230
YS12-N18A-A*	Y50-N18A-A	20	205	87	166	7.39	2.00		6	230
YS12-30CL-B	YB30CL-B	30	168	132	192	10.33	3.00		9	280
YS60-N30L-BS	Y60-N30L-A/Y60-N30L-B	30	186	130	170	9.42	3.00		3	300
YS12-4A-BS	YTR4A-BS	2.5	110	47	85	1.05	0.25		10	30
YS12-4B-BS	YT4B-BS/YT4B-BS	2.3	113	39	86	0.95	0.23		11	30
YS12-4L-BS	YTX4L-BS/YTZ3S	4	113	69	85	1.41	0.40		9	45
YS12-5L-BS	YTX5L-BS	5	113	69	105	1.78	0.50		9	75
YS12-7L-BS	YTX7L-BS	7	113	69	130	2.39	0.70		9	100
YS12-7A-BS	YTX7A-BS	7	150	86	94	2.46	0.70		9	105

YS12-9-BS	YTX9-BS	9	150	86	105	3.14	0.90	HTTF	9	120
YS12-9L-BS	YTX9L-BS	9	150	86	105	3.14	0.90	HTTF	9	120
YS12-12A-BS	YT12A-BS	10	151	87	105	3.29	1.00	HTTF	9	120
YS12-12-BS	YTX12-BS	12	150	86	130	4.02	1.20	HTTF	9	140
YS12-12L-BS	YTX12L-BS	12	150	86	130	4.02	1.20	HTTF	9	140
YS12-14-BS	YTX14-BS	14	150	86	145	4.54	1.40	HTTF	9	170
YS12-14L-BS	YTX14L-BS	14	150	86	145	4.54	1.40	HTTF	9	170
YS12-15-BS	YTX15-BS	14	175	87	130	4.77	1.40	HTTF	4	180
YS12-15L-BS	YTX15L-BS	14	175	87	130	4.77	1.40	HTTF	4	180
YS12-16-BS	YTX16-BS	16	150	86	161	5.17	1.60	HTTF	9	185
YS12-16L-BS	YTX16L-BS	16	150	86	161	5.17	1.60	HTTF	9	185
YS12-18-BS	YTX18-BS	20	205	87	162	7.39	2.00	HTTF	4	230
YS12-18L-BS	YTX18L-BS	20	205	87	162	7.39	2.00	HTTF	4	230
YS12-19-BS	YB16-B	19	175	100	155	6.40	1.90	HTTF	4	190
YS12-19L-BS	YB16L-B	19	175	100	155	6.40	1.90	HTTF	4	190
YS12-19CL-BS	YB16CL-B	21	175	100	175	7.49	2.10	HTTF	4	210
YS12-20CH-BS	YTX20CH-BS	18	151	87	161	5.89	1.80	HTTF	9	180
YS12-20-BS	YTX20-BS	20	175	87	154	6.21	2.00	HTTF	9	230
YS12-20L-BS	YTX20L-BS	20	175	87	154	6.21	2.00	HTTF	9	230
YS12-20H-BS	YTX20H-BS	20	175	87	154	6.21	2.00	HTTF	9	230
YS12-20HL-BS	YTX20HL-BS	20	175	87	154	6.21	2.00	HTTF	9	230
YS12-24HL-BS	YTX24HL-BS	24	205	87	162	7.41	2.40	HTTF	4	300
YS12-30-BS	YIX30-BS	30	167	127	176	9.43	3.00	HTTF	4	300
YS12-30L-BS	YIX30L-BS	30	167	127	176	9.43	3.00	HTTF	4	300
YS52430	12N24-3/12N24-3A	24	178	123	166	7.62	2.40	HTTF	3	240
YS52434	12N24-4/12N24-4A	24	178	123	166	7.62	2.40	HTTF	3	240
YS53030	53030	28	178	123	166	8.52	2.80	HTTF	3	280
YS53034	53034	28	178	123	166	8.52	2.80	HTTF	3	280
YT7B-4	YT7B-4/YT7B-BS	6	150	65	92	2.42	0.60	HTTF	9	85
YT9B-4	YT9B-4/YT9B-BS	8	150	69	105	2.93	0.80	HTTF	9	100
YT12B-4	YT12B-4/YT12B-BS	10	150	69	130	3.64	1.00	HTTF	9	105
YT14B-4	YT14B-4/YT14B-BS	12	150	69	145	4.23	1.20	HTTF	9	135
YTZ3S	YTZ5S	3	114	70	85	1.39	0.30	HTTF	4	30
YTZ5S	YTZ5S	4	113	69	85	1.43	0.40	HTTF	9	50
YTZ6S	YTZ6S	6	114	71	106	2.27	0.60	HTTF	9	75
YT6B-3	YT6B-3	6	114	71	106	1.92	0.60	HTTF	9	75
YTZ7S	YTZ7S	6	113	69	105	1.92	0.60	HTTF	9	75
YTZ10S	YTZ10S	8.6	150	86	94	2.75	0.86	HTTF	9	120
YTZ12S	YTZ12S	11	150	86	110	3.35	1.12	HTTF	9	140
YTZ14S	YTZ14S	11.2	150	86	110	3.35	1.12	HTTF	9	140
YTZ15S	YTZ15S	15	150	87	144	4.81	1.50	HTTF	23	170
YTZ16S	GYZ16H	16	150	86	145	4.60	1.60	HTTF	9	185

*The height includes 4mm spacer △ 20 hour rate