




Pin No	Symbol
1	CS
2	RST
3	RS
4	WR
5	RD
6-13	D0-D7
14	VDD
15	VSS
16	NC
17	NC
18	NC
19	NC
20	V0
21	XV0
22	NC
23	NC
24	NC
25	NC
26	VOUT
27	NC
28	C86
29	P\S
30	NC



NOTES:

1. DISPLAY TYPE: STN
2. LCD OPERATING VOLT: 7V
3. DRIVE MODE: 1/64 Duty1/9 Bias
4. VIEWING DIRECTION: 6 O'CLOCK
5. OPERATING TEMP: -20°C~70°C
6. STORAGE TEMP: -30°C~80°C
7. POLARIZER MODE: COG+IC(ST7667)
8. CONNECTOR: SG128645-FCGNX
9. CUSTOMER'S MODEL NO. :符合“RoHS”要求
10. ROHS :
11. 丝印 :

RODITI  
SD128646-FCGNX

SHEET: 1 OF 1		<div>LCDALCM 400</div> <div>松本國際股份有限公司</div> <div>SOOBOO INTERNATIONAL CO.,LTD</div>	
GENERAL TOL: ±0.20 MM	UNITS MM		
CUS NO:		MODULE NUMBER:  SD128646-FCGNX	
DRAW BY:	XM		
CHK BY:	QIN		
APP BY:	100	DO NOT SCALE THIS DRAWING.	
		<div></div>	
		TEL:400-860-1710	
		FAX:0556-4371082	
		DATE: 2019-5-15	