

钢芯或钢丝编织带的选择


Choice of steel core or wire carrier

当使用钢芯或者钢丝编织带时，在不使用接续胶带的情况下，棱边保护部分可以紧紧抓住物体，但是，钢芯的夹持效果要比金属丝线送装置更好。

对于带有一个不间断的钢芯的异型材而言，它的缺点是在测刃上弯曲半径会受到限制，这个问题可以通过去掉连续用桥件的方法得到解决。但是，这样又会使绳股上的压力出现轻微的不均匀的现象，对于大多数工程应用而言，这种外观并不会对实际造成太大影响。选择钢芯还是钢丝编辑带是由每一种应用情况以及所要求的外观所决定的。

When using steel core or wire carrier, the pronged protective section can grip the object tightly without the use of splicing tape, however. Steel cores hold better than wire devices.


For profiles with an uninterrupted steel core. It has the disadvantage that the bending radius on the measuring edge will be limited, a problem that can be solved by removing the continuous use of the bridge piece. However, this again results in a slightly uneven pressure on the rope strands, which for most engineering applications, this appearance does not have much practical impact. The choice between steel core or steelwire edited tape is determined by each application and the required appearance.




钢丝编织带
Wire Carrier



单桥冲切钢片
Steel Carrier



双桥冲切钢片
Steel Carrier




双桥滚压钢片
Steel Carrier

产品装配步骤、说明:

Product assembly steps, instructions

产品系列
Product range



90°直角需要把密封条弯曲安装，如下图：
The 90° right angle requires the dense strip to be bent and installed as shown below



此款密封条主要用于工业机箱柜密封作用，唇形设计，只需稍微压缩便可以完全起到密封作用。

独特的设计可以防止在开门时脱落，并能保持均匀的密封压力。

主要性能如下：温度范围：+120℃至-40℃，耐老化，耐紫外线，臭氧和海洋性气候。

设计参数：钢板尺寸：1.5mm，2.0mm,钢板间距需考虑压缩量。

This dense strip is mainly used for sealing industrial enclosures and cabinets. The lip design allows the dense strip to be fully compressed with only a slight compression. The unique design prevents dislodgement when opening doors and maintains an even sealing pressure. The main properties are as follows: temperature range: +120C to -40C, ageing resistance, UV, ozone and marine weather resistance. Design parameters: Steel plate size: 1.5mm, 2.0mm, spacing should be taken into account compression.



错误的使用方法描述：

图1、不合理的钢板设计（钢板有料度）；图2、钢板平面呈波浪形。

如果这两种情况，能达到最大压缩量的50%，也是可以达到密封的作用。

类似这样使用是不对的，需要专业的技术指导。



Description of incorrect use:

Fig. 1. Unreasonable steel plate design (steel plate with materiality); Fig. 2. Steel plate with a wavy plane.

If in both cases, 50% of the maximum compression can be achieved, it is also possible to achieve the sealing effect. It is not correct to use it in a similar way and requires professional technical guidance.

▶ 开口度产品的正确使用方法
The correct way to use products with openings

对于有些密封条基底软胶开口部分内嵌钢丝或钢带（钢芯）将产品卡入其内不但保护产品边缘锐利部分，此密封条的泡胶部分还起到了密封作用，此类开口处内嵌钢丝的密封条开口度的确定要经过插入里（N）、拔出里（N）的检测设备进行开口度的数据检测，不可凭借手感。

图例：产品开口度的大小会因装配方式和人员力度的不同而产生误差。

For some dense strip base soft rubber opening part embedded steel wire or steel belt (steel core) will be stuck into the product not only to protect the sharp part of the product edge, the bubble rubber part of this dense strip also plays a sealing role, such openings embedded steel wire seal opening degree of determination should be inserted into the (N), pull out the (N) testing equipment for the opening degree of data testing. It is not a matter of feel. Illustration: The size of the product opening can be misleading depending on the assembly method and the strength of the personnel.

1.内嵌钢丝带的密封条开口度尺寸要使用不同拔插力（N）来检测确定开口度的适用性。


如下表

1. The size of the opening of a seal with an embedded steel strip is tested using different pull-out forces (N) to determine the suitability of the opening. The table below shows

产品开口度 Product opening	板厚 Plate thickness	插入力 Insertion force	拔出力 Extraction force
1.50mm	2.00mm	40N-60N	120N-160N

2.以下是内嵌钢丝带的产品安装图示：

The following diagrams show the installation of the products with embedded wire straps



▶ 背胶产品的使用说明：
Instructions for the use of adhesive-backed products

使用方法
How to use

- 1.清洁粘接基体，保证基体表面清洁、干燥
 - 2.对齐粘接基体，将产品平稳粘接于基体表面，请勿用尖锐物体重击表面。
 - 3.为增强粘接效果，建议在粘接基体上涂上底涂剂。
1. Clean the substrate, ensure the surface is clean and dry.
 2. Align the substrate and bond the product smoothly to the substrate surface, do not hit the surface with sharp objects.
 3. To enhance the bonding effect, it is recommended that a primer is applied to the substrate.

注意事项
Cautions

- 1.粘接基体表面需干净、干燥
 - 2.贴附时压力不可太大
 - 3.当产品贴于客户基体时不可取下再次利用
 - 4.产品在收盘储存时不要随意堆放，以防起皱（如右图所示）
1. The surface of the bonding substrate must be clean and dry
 2. Do not apply too much pressure when attaching
 3. The product should not be removed for re-use when it is applied to the customer's substrate
 4. Do not stack the products in the storage tray to prevent wrinkling (as shown in the picture on the right)

底涂使用
Primer application

- 1.使用底涂可以有效改善胶带的初粘性和终粘性。
 - 2.底涂涂布要均匀。
 - 3.涂上底涂后要充分的晾干（室温下 > 5分钟），然后才能进行胶带粘接。
1. The use of primer will improve the initial and final adhesion of the tape.
 2. The primer should be applied evenly.
 3. Allow to dry well after applying the primer (>5 minutes at room temperature) before the tape can be bonded.

黏贴注意事项
Notes on gluing



弯曲弧度小粘贴不被推荐
原因：橡胶弧度小伸缩性拉力大，导致双面胶粘不牢翘起。
Small curvature is not recommended
Reason: The small curvature of the rubber has a large stretching force and causes the double-sided adhesive to buckle.



弯曲弧度大勉强可以
原因：弧度大，伸缩性拉力小，粘度大于伸缩力。
Large curvature is barely acceptable
Reason: Large curvature, small stretching force. The adhesive force is greater than the stretching force.



正常储存
Normal storage



起皱
Wrinkling



底涂剂
Primer

► 密封条的编码规则

The naming rules of seal strips

MFT1001—MFT1024	自夹紧式钢带密封条 Self-gripping Sealing Strip With Steel Sheet
MFT1025—MFT1054	挤出型三元乙丙海绵胶条 Extruded EPDM Sponge Strip
MFT1055—MFT1078	挤出型三元乙丙密实胶条 Extruded EPDM Dense Strip
MFT1079—MFT1118	海绵发泡密封条 Foam Sponge strip
MFT1119—MFT1123	观察窗密封条 Observation Window Sealing Strip
MFT1124—MFT1128	电缆穿线护套 Cable threading sheath
MFT1129—MFT1138	海绵发泡胶条 Sponge Foam Tape
MFT1139—MFT1150	过线胶圈 Thread passing rubber ring
MF1001—MF1018	自夹紧式钢丝密封条 Self-gripping Sealing Strip With Steel Wire
MF1019—MF1030	PVC 橡塑装饰条 PVC Trim Strip
MF1031—MF1032	密封胶条 Rubber Sealing Strip

下列从各种不同标准中汇编而成的公差等级主要用于快速指定允许的尺寸偏差。这些公差等级不适用于公差已经固定的图纸。

The following tolerance classes, compiled from various standards, are intended primarily for the quick specification of permissible dimensional deviations. These tolerance classes do not apply to drawings where the tolerances are already fixed.

根据DIN 16941 3A and 3B 标准的 PVC 异型材（横截面）PVC profiles (cross-sections) according to DIN 16941 3A and 3B



标称范围 单位：毫米 Nominal range in mm				+/-毫米 +/- mm
	up to		3	0.4
>	3	to	6	0.6
>	6	to	10	0.7
>	10	to	18	0.8
>	18	to	30	1.0
>	30	to	50	1.2
>	50	to	80	1.5
>	80	to	120	1.9
>	120	to	180	2.3
>	180	to	250	2.8
>	250	to	320	3.5
>	320			1.4%

根据DIN 16941 4B 标准，用于订制长度（PVC）的公差 According to DIN 169414B. Tolerances for customised lengths (PVC)



标称范围 单位：毫米 Nominal range in mm				+/-毫米 +/- mm
	up to		400	5.0
>	400	to	1000	10.0
>	1000	to	2500	20.0
>	2500	to	6000	30.0
>	6000	to		2%

产品系列： MFT-1001/1002/1003/1004/1005/1006



Product series





MFT-1001
黑色三元乙丙钢带密封条
Black EPDM sealing strip(with steel sheet)





MFT-1002
黑色三元乙丙钢带密封条
Black EPDM sealing strip(with steel sheet)





MFT-1003
黑色三元乙丙钢带密封条
Black EPDM sealing strip(with steel sheet)



MFT-1004
黑色三元乙丙无钢带密封条
Black EPDM sealing strip(no steel sheet)



MFT-1005
黑色三元乙丙钢带密封条
Black EPDM sealing strip(with steel sheet)



MFT-1006
黑色三元乙丙钢带密封条
Black EPDM sealing strip(with steel sheet)

EPDM海绵硬度：30±5 Shore A；EPDM密实硬度：65±5 Shore A，可根据客户要求定制阻燃、绝缘、导电等特性胶条
EPDM sponge hardness: 30 ± 5 Shore A; EPDM compactness hardness: 65 ± 5 Shore A, and the adhesive strips with flame retardant, insulating, conductive and other characteristics can be customized according to customers

产品系列： MFT-1007/1008/1009/1010/1011/1012
Product series

MFT-1007
黑色三元乙丙钢带密封条
Black EPDM sealing strip(with steel sheet)

MFT-1008
黑色三元乙丙钢带密封条
Black EPDM sealing strip(with steel sheet)

MFT-1009
黑色三元乙丙钢带密封条
Black EPDM sealing strip(with steel sheet)

MFT-1010
黑色三元乙丙钢带密封条
Black EPDM sealing strip(with steel sheet)

MFT-1011
黑色三元乙丙钢带密封条
Black EPDM sealing strip(with steel sheet)

MFT-1012
黑色三元乙丙钢带密封条
Black EPDM sealing strip(with steel sheet)

EPDM海绵硬度：30±5 Shore A； EPDM密实硬度：65±5 Shore A，可根据客户要求定制阻燃、绝缘、导电等特性胶条
EPDM sponge hardness: 30 ± 5 Shore A; EPDM compactness hardness: 65 ± 5 Shore A, and the adhesive strips with flame retardant, insulating, conductive and other characteristics can be customized according to customers

产品系列： MFT-1013/1014/1015/1016/1017/1018
Product series

MFT-1013
黑色三元乙丙钢带密封条
Black EPDM sealing strip(with steel sheet)

MFT-1014
黑色三元乙丙钢带密封条
Black EPDM sealing strip(with steel sheet)

MFT-1015
黑色三元乙丙钢带密封条
Black EPDM sealing strip(with steel sheet)

MFT-1016
黑色三元乙丙密实发泡密封条
Black EPDM sealing strip













MFT-1017
黑色三元乙丙钢带密封条
Black EPDM sealing strip(with steel sheet)

MFT-1018
黑色三元乙丙钢带密封条
Black EPDM sealing strip(with steel sheet)

EPDM海绵硬度：30±5 Shore A； EPDM密实硬度：65±5 Shore A，可根据客户要求定制阻燃、绝缘、导电等特性胶条
EPDM sponge hardness: 30 ± 5 Shore A; EPDM compactness hardness: 65 ± 5 Shore A, and the adhesive strips with flame retardant, insulating, conductive and other characteristics can be customized according to customers

自夹紧式钢带密封条 Self-gripping Sealing Strip With Steel Sheet












产品系列： MFT-1019/1020/1021/1022/1023/1024
Product series

  <p>MFT-1019 黑色三元乙丙钢带密封条 Black EPDM sealing strip(with steel sheet)</p>	  <p>MFT-1020 黑色三元乙丙钢带密封条 Black EPDM sealing strip(with steel sheet)</p>	  <p>MFT-1021 黑色三元乙丙钢带密封条 Black EPDM sealing strip(with steel sheet)</p>
  <p>MFT-1022 黑色三元乙丙钢带密封条 Black EPDM sealing strip(with steel sheet)</p>	  <p>MFT-1023 黑色三元乙丙钢片密封条 Black EPDM sealing strip(with steel sheet)</p>	  <p>MFT-1024 黑色三元乙丙密封条 Black EPDM sealing strip</p>

EPDM海绵硬度：30±5 Shore A； EPDM密封硬度：65±5 Shore A， 可根据客户要求定制阻燃、绝缘、导电等特性胶条
EPDM sponge hardness: 30 ± 5 Shore A; EPDM compactness hardness: 65 ± 5 Shore A, and the adhesive strips with flame retardant, insulating, conductive and other characteristics can be customized according to customers

挤出型三元乙丙海绵胶条 Extruded EPDM Sponge Strip



产品系列： MFT-1025/1026/1027/1028/1029/1030
Product series

  <p>MFT-1025 黑色三元乙丙海绵胶条 Black EPDM Sponge Strip</p>	  <p>MFT-1026 黑色三元乙丙海绵胶条 Black EPDM Sponge Strip</p>	  <p>MFT-1027 黑色三元乙丙海绵胶条 Black EPDM Sponge Strip</p>
  <p>MFT-1028 黑色三元乙丙海绵胶条 Black EPDM Sponge Strip</p>	  <p>MFT-1029 黑色三元乙丙海绵胶条 Black EPDM Sponge Strip</p>	  <p>MFT-1030 黑色三元乙丙海绵胶条 Black EPDM Sponge Strip</p>



EPDM海绵硬度：30±5 Shore A； EPDM密封硬度：65±5 Shore A， 可根据客户要求定制阻燃、绝缘、导电等特性胶条
EPDM sponge hardness: 30 ± 5 Shore A; EPDM compactness hardness: 65 ± 5 Shore A, and the adhesive strips with flame retardant, insulating, conductive and other characteristics can be customized according to customers

挤出型三元乙丙海绵胶条 Extruded EPDM Sponge Strip



产品系列：MFT-1031/1032/1033/1034/1035/1036
Product series



MFT-1031
黑色三元乙丙海绵胶条
Black EPDM Sponge Strip



MFT-1032
黑色三元乙丙海绵胶条
Black EPDM Sponge Strip



MFT-1033
黑色三元乙丙海绵胶条
Black EPDM Sponge Strip

MFT-1034
黑色三元乙丙海绵胶条
Black EPDM Sponge Strip

MFT-1035
黑色三元乙丙海绵胶条
Black EPDM Sponge Strip






MFT-1036
黑色三元乙丙海绵胶条
Black EPDM Sponge Strip



EPDM海绵硬度：30±5 Shore A；EPDM密实硬度：65±5 Shore A，可根据客户要求定制阻燃、绝缘、导电等特性胶条
EPDM sponge hardness: 30 ± 5 Shore A; EPDM compactness hardness: 65 ± 5 Shore A, and the adhesive strips with flame retardant, insulating, conductive and other characteristics can be customized according to customers

挤出型三元乙丙海绵胶条 Extruded EPDM Sponge Strip



产品系列：MFT-1037/1038/1039/1040/1041/1042
Product series



MFT-1037
黑色三元乙丙海绵胶条
Black EPDM Sponge Strip

MFT-1038
黑色三元乙丙海绵胶条
Black EPDM Sponge Strip

MFT-1039
EPDM密封胶圈
EPDM Sealing O-ring

MFT-1040
黑色三元乙丙海绵胶条
Black EPDM Sponge Strip
















MFT-1041
黑色三元乙丙海绵胶条
Black EPDM Sponge Strip




MFT-1042
黑色三元乙丙海绵胶条
Black EPDM Sponge Strip













EPDM海绵硬度：30±5 Shore A；EPDM密实硬度：65±5 Shore A，可根据客户要求定制阻燃、绝缘、导电等特性胶条
EPDM sponge hardness: 30 ± 5 Shore A; EPDM compactness hardness: 65 ± 5 Shore A, and the adhesive strips with flame retardant, insulating, conductive and other characteristics can be customized according to customers

产品系列： MFT-1043/1044/1045/1046/1047/1048
Product series

  <p>MFT-1043 EPDM门用缓冲钉 EPDM door nail buffer</p>	  <p>MFT-1044 EPDM门用缓冲钉 EPDM door nail buffer</p>	  <p>MFT-1045 黑色三元乙丙海绵胶条 Black EPDM Sponge Strip</p>
  <p>MFT-1046 黑色三元乙丙海绵胶条 Black EPDM Sponge Strip</p>	  <p>MFT-1047 黑色三元乙丙海绵胶条 Black EPDM Sponge Strip</p>	  <p>MFT-1048 黑色三元乙丙海绵胶条 Black EPDM Sponge Strip</p>

EPDM海绵硬度：30±5 Shore A； EPDM密实硬度：65±5 Shore A，可根据客户要求定制阻燃、绝缘，导电等特性胶条
EPDM sponge hardness: 30 ± 5 Shore A; EPDM compactness hardness: 65 ± 5 Shore A, and the adhesive strips with flame retardant, insulating, conductive and other characteristics can be customized according to customers

产品系列： MFT-1049/1050/1051/1052/1053/1054
Product series

  <p>MFT-1049 黑色三元乙丙海绵胶条 Black EPDM Sponge Strip</p>	  <p>MFT-1050 黑色三元乙丙海绵胶条 Black EPDM Sponge Strip</p>	  <p>MFT-1051 黑色三元乙丙海绵胶条 Black EPDM Sponge Strip</p>
  <p>MFT-1052 黑色三元乙丙海绵胶条 Black EPDM Sponge Strip</p>	  <p>MFT-1053 黑色三元乙丙海绵胶条 Black EPDM Sponge Strip</p>	  <p>MFT-1054 黑色三元乙丙海绵胶条 Black EPDM Sponge Strip</p>

EPDM海绵硬度：30±5 Shore A； EPDM密实硬度：65±5 Shore A，可根据客户要求定制阻燃、绝缘，导电等特性胶条
EPDM sponge hardness: 30 ± 5 Shore A; EPDM compactness hardness: 65 ± 5 Shore A, and the adhesive strips with flame retardant, insulating, conductive and other characteristics can be customized according to customers

挤出型三元乙丙密实胶条 Extruded EPDM Dense Strip

产品系列： MFT-1055/1056/1057/1058/1059/1060
Product series

MFT-1055
黑色三元乙丙密实胶条
Black EPDM Dense Strip

MFT-1056
黑色三元乙丙密实胶条
Black EPDM Dense Strip

MFT-1057
PVC密封胶条
PVC gasketing

MFT-1058
黑色三元乙丙密实胶条
Black EPDM Dense Strip

MFT-1059
黑色三元乙丙密实胶条
Black EPDM Dense Strip

MFT-1060
黑色三元乙丙密实胶条
Black EPDM Dense Strip

EPDM海绵硬度：30±5 Shore A；EPDM密实硬度：65±5 Shore A，可根据客户要求定制阻燃、绝缘、导电等特性胶条
EPDM sponge hardness: 30 ± 5 Shore A; EPDM compactness hardness: 65 ± 5 Shore A, and the adhesive strips with flame retardant, insulating, conductive and other characteristics can be customized according to customers

挤出型三元乙丙密实胶条 Extruded EPDM Dense Strip

产品系列： MFT-1061/1062/1063/1064/1065/1066
Product series

MFT-1061
黑色三元乙丙密实胶条
Black EPDM Dense Strip

MFT-1062
黑色三元乙丙密实胶条
Black EPDM Dense Strip

MFT-1063
黑色三元乙丙密实胶条
Black EPDM Dense Strip

MFT-1064
黑色三元乙丙密实胶条
Black EPDM Dense Strip



MFT-1065
PVC密封胶条
PVC gasketing

MFT-1066
黑色三元乙丙密实胶条
Black EPDM Dense Strip



EPDM海绵硬度：30±5 Shore A；EPDM密实硬度：65±5 Shore A，可根据客户要求定制阻燃、绝缘、导电等特性胶条
EPDM sponge hardness: 30 ± 5 Shore A; EPDM compactness hardness: 65 ± 5 Shore A, and the adhesive strips with flame retardant, insulating, conductive and other characteristics can be customized according to customers

挤出型三元乙丙密实胶条 Extruded EPDM Dense Strip



产品系列：MFT-1067/1068/1069/1070/1071/1072
Product series



MFT-1067
黑色三元乙丙密实胶条
Black EPDM Dense Strip



MFT-1068
黑色三元乙丙密实胶条
Black EPDM Dense Strip



MFT-1069
黑色三元乙丙密实胶条
Black EPDM Dense Strip

MFT-1070
黑色三元乙丙密实胶条
Black EPDM Dense Strip

MFT-1071
黑色三元乙丙密实胶条
Black EPDM Dense Strip






MFT-1072
黑色三元乙丙密实胶条
Black EPDM Dense Strip



EPDM海绵硬度：30±5 Shore A；EPDM密实硬度：65±5 Shore A，可根据客户要求定制阻燃、绝缘、导电等特性胶条
EPDM sponge hardness: 30 ± 5 Shore A; EPDM compactness hardness: 65 ± 5 Shore A, and the adhesive strips with flame retardant, insulating, conductive and other characteristics can be customized according to customers

挤出型三元乙丙密实胶条 Extruded EPDM Dense Strip



产品系列：MFT-1073/1074/1075/1076/1077/1078
Product series

MFT-1073
黑色三元乙丙密实胶条
Black EPDM Dense Strip

MFT-1074
黑色三元乙丙密实胶条
Black EPDM Dense Strip

MFT-1075
黑色三元乙丙密实胶条
Black EPDM Dense Strip




MFT-1076
黑色三元乙丙密实胶条
Black EPDM Dense Strip





MFT-1077
黑色三元乙丙密实胶条
Black EPDM Dense Strip




MFT-1078
黑色三元乙丙密实胶条
Black EPDM Dense Strip

EPDM海绵硬度：30±5 Shore A；EPDM密实硬度：65±5 Shore A，可根据客户要求定制阻燃、绝缘、导电等特性胶条
EPDM sponge hardness: 30 ± 5 Shore A; EPDM compactness hardness: 65 ± 5 Shore A, and the adhesive strips with flame retardant, insulating, conductive and other characteristics can be customized according to customers


产品系列：Product series



海绵发泡方形密封条 Foam Sponge square strip

代号 Code	C	D	代号 Code	C	D
MFT-1079	1.5	18	MFT-1095	4	15
MFT-1080	2	10	MFT-1096	4	20
MFT-1081	2	12	MFT-1097	4	25
MFT-1082	2	15	MFT-1098	4	30
MFT-1083	2	20	MFT-1099	5	10
MFT-1084	3	6	MFT-1100	5	12
MFT-1085	3	10	MFT-1101	5	14
MFT-1086	3	12	MFT-1102	5	15
MFT-1087	3	15	MFT-1103	5	20
MFT-1088	3	18	MFT-1104	5	30
MFT-1089	3	20	MFT-1105	6	10
MFT-1090	3	25	MFT-1106	6	15
MFT-1091	3	30	MFT-1107	6	17
MFT-1092	3	35	MFT-1108	6	20
MFT-1093	4	10	MFT-1109	6	25
MFT-1094	4	12	MFT-1110	6	30

注：背面胶带可选择进口综研胶带、网格纤维胶带、3M胶带或者其他品牌胶带。
Note: the back tape can be imported comprehensive research tape, network fiber tape, 3M tape or other brand tape






海绵发泡圆形密封条 Foam Sponge round strip

代号 Code	Ø
MFT-1111	3
MFT-1112	4
MFT-1113	5
MFT-1114	6
MFT-1115	7
MFT-1116	8
MFT-1117	9
MFT-1118	10

EPDM海绵硬度：30±5 Shore A；EPDM密实硬度：65±5 Shore A，可根据客户要求定制阻燃、绝缘、导电等特性胶条
EPDM sponge hardness: 30 ± 5 Shore A; EPDM compactness hardness: 65 ± 5 Shore A, and the adhesive strips with flame retardant, insulating, conductive and other characteristics can be customized according to customers




产品系列：Product series



观察窗胶条 Observation Window Sealing Strip

代号 Code	B	H	H1	H2	H3
MFT-1119	29	23	5	2	8
MFT-1120	26	18	5	2	5
MFT-1121	21	17	5	2	5
MFT-1122	19	14	4	1.5	4
MFT-1123	15	10	3	3	3




电缆穿线护套 Cable threading sheath

代号 Code	开孔尺寸(A) Recommended hole size	B	C
MFT-1124	28	38	36
MFT-1125	50	60	46
MFT-1126-1	60	70	46
MFT-1126-2	70	75	50
MFT-1127-1	80	88	60
MFT-1127-2	100	110	62
MFT-1128	110	122	60

EPDM海绵硬度：30±5 Shore A；EPDM密实硬度：65±5 Shore A，可根据客户要求定制阻燃、绝缘、导电等特性胶条
EPDM sponge hardness: 30 ± 5 Shore A; EPDM compactness hardness: 65 ± 5 Shore A, and the adhesive strips with flame retardant, insulating, conductive and other characteristics can be customized according to customers




产品系列：Product series



发泡半圆胶条 Foam half-round tape

代号 Code	A	B	代号 Code	A	B
MFT-1129	16	3	MFT-1134	12	10
MFT-1130	16	5	MFT-1135	10	12
MFT-1131	16	6.5	MFT-1136	10	6.5
MFT-1132	16	7	MFT-1137	11	7
MFT-1133	16	8	MFT-1138	11	12

注：背面胶带可选择进口综研胶带、网格纤维胶带、3M胶带或者其他品牌胶带。
Note: the back tape can be imported comprehensive research tape, network fiber tape, 3M tape or other brand tape




过线胶圈 Thread passing rubber ring

代号 Code	开孔尺寸(D) Recommended hole size	D1	D2	D3
MFT-1139	10	15	8	7
MFT-1140	22	32	20	9
MFT-1141	24	29	18	7
MFT-1142	32	40	22	8
MFT-1143	35	44	29	7
MFT-1144	40	49	33	9
MFT-1145	45	52	37	7
MFT-1146	50	64	45	8
MFT-1147	60	70	51	8
MFT-1148	80	88	66	9
MFT-1149	100	106	86	12
MFT-1150	110	116	95	12




EPDM海绵硬度：30±5 Shore A；EPDM密实硬度：65±5 Shore A，可根据客户要求定制阻燃、绝缘、导电等特性胶条
EPDM sponge hardness: 30 ± 5 Shore A; EPDM compactness hardness: 65 ± 5 Shore A, and the adhesive strips with flame retardant, insulating, conductive and other characteristics can be customized according to customers

产品系列：Product series MF-1001/1002/1003/1004/1005/1006




MF-1001

黑色三元乙丙钢丝胶条
Black EPDM steel wire strip





MF-1002

黑色三元乙丙钢丝胶条
Black EPDM steel wire strip





MF-1003

黑色三元乙丙钢丝胶条
Black EPDM steel wire strip





MF-1004

黑色三元乙丙钢丝胶条
Black EPDM steel wire strip



MF-1005

黑色三元乙丙钢丝胶条
Black EPDM steel wire strip



MF-1006

黑色三元乙丙钢丝胶条
Black EPDM steel wire strip

EPDM海绵硬度：30±5 Shore A；EPDM密实硬度：65±5 Shore A，可根据客户要求定制阻燃、绝缘、导电等特性胶条
EPDM sponge hardness: 30 ± 5 Shore A; EPDM compactness hardness: 65 ± 5 Shore A, and the adhesive strips with flame retardant, insulating, conductive and other characteristics can be customized according to customers

自夹紧式钢丝密封条 Self-gripping Sealing Strip With Steel Wire

产品系列：MF-1007/1008/1009/1010/1011/1012
Product series

 MF-1007 黑色三元乙丙钢丝胶条 Black EPDM steel wire strip	 MF-1008 黑色三元乙丙钢丝胶条 Black EPDM steel wire strip	 MF-1009 黑色三元乙丙钢丝胶条 Black EPDM steel wire strip
 MF-1010 黑色三元乙丙钢丝胶条 Black EPDM steel wire strip	 MF-1011 黑色三元乙丙钢丝胶条 Black EPDM steel wire strip	 MF-1012 黑色三元乙丙钢丝胶条 Black EPDM steel wire strip

EPDM海绵硬度：30±5 Shore A；EPDM密实硬度：65±5 Shore A，可根据客户要求定制阻燃、绝缘、导电等特性胶条
 EPDM sponge hardness: 30 ± 5 Shore A; EPDM compactness hardness: 65 ± 5 Shore A, and the adhesive strips with flame retardant, insulating, conductive and other characteristics can be customized according to customers

自夹紧式钢丝密封条 Self-gripping Sealing Strip With Steel Wire

产品系列：MF-1013/1014/1015/1016/1017/1018
Product series


 MF-1013 黑色三元乙丙钢丝胶条 Black EPDM steel wire strip	 MF-1014 黑色三元乙丙钢丝胶条 Black EPDM steel wire strip	 MF-1015 黑色三元乙丙钢丝胶条 Black EPDM steel wire strip
 MF-1016 黑色三元乙丙钢丝胶条 Black EPDM steel wire strip	 MF-1017 黑色三元乙丙钢丝胶条 Black EPDM steel wire strip	 MF-1018 黑色三元乙丙钢丝胶条 Black EPDM steel wire strip

EPDM海绵硬度：30±5 Shore A；EPDM密实硬度：65±5 Shore A，可根据客户要求定制阻燃、绝缘、导电等特性胶条
 EPDM sponge hardness: 30 ± 5 Shore A; EPDM compactness hardness: 65 ± 5 Shore A, and the adhesive strips with flame retardant, insulating, conductive and other characteristics can be customized according to customers

PVC橡塑装饰条 PVC Trim Strip


产品系列：MF-1019/1020/1021/1022/1023/1024

Product series




MF-1019

PVC橡塑装饰条
PVC trim strip




MF-1020

PVC橡塑装饰条
PVC trim strip





MF-1021

PVC橡塑装饰条
PVC trim strip





MF-1022

PVC橡塑装饰条
PVC trim strip



MF-1023

PVC橡塑装饰条
PVC trim strip



MF-1024


PVC橡塑装饰条
PVC trim strip

PVC边缘保护条，肖氏硬度：60±5 Shore A
PVC edge protection strip, shore hardness: 60 ± 5 shore A

PVC橡塑装饰条 PVC Trim Strip



产品系列：MF-1025/1026/1027/1028/1029/1030

Product series





MF-1025

PVC橡塑装饰条
PVC trim strip





MF-1026

PVC橡塑装饰条
PVC trim strip




MF-1027

PVC橡塑装饰条
PVC trim strip




MF-1028

PVC橡塑装饰条
PVC trim strip



MF-1029

PVC橡塑装饰条
PVC trim strip




MF-1030



PVC橡塑装饰条
PVC trim strip

PVC边缘保护条，肖氏硬度：60±5 Shore A
PVC edge protection strip, shore hardness: 60 ± 5 shore A


产品系列：MF-1031/1032
Product series



黑色发泡EPDM唇型密封胶条,肖氏硬度:30±5 Shore A Black foaming EPDM lip sealant strip, Shore hardness: 30 ± 5 Shore A					
AH	高度H	代号 Code	AH	高度H	代号 Code
16	18.5	MF-1031	22	24.5	MF-1031
18	20.5	MF-1031	24	26.5	MF-1031
20	22.5	MF-1031	26	28.5	MF-1031



黑色CREPDM唇型密封胶条,肖氏硬度:65±5 Shore A Black CR EPDM lip sealant strip, Shore hardness: 65 ± 5 Shore A									
AH	H	h	个数	代号	AH	H	h	个数	代号
16	17	9.5	1	MF-1032	20	21	13.5	2	MF-1032
18	19	11.5	1	MF-1032	26	27	19.5	3	MF-1032




钢夹顶条
Steel clamp top strip




钢夹侧条
Steel clip side strip



边缘条
Edge bar



简易型条
Simple shaped bar



卡夹条
Clip strip



嵌入条
Embedded bar

除目录书规格外我们还可以为您定制, 欢迎来电咨询!
In addition to the catalogue, we can also customize it for you. Welcome to inquire