

HQ-ZY4C1 液体灌装旋盖机 Automatic liquid filling-capping machine:



简要介绍 Brief introduction:

- ✧ 灌装旋(轧)盖机是我公司传统系列灌装封口设备，适用于各种圆形、异形瓶的灌装旋（轧）盖。
- ✧ 可对不同高粘度流体进行灌装,根据物料的不同，可选择采用金属泵、玻璃泵、陶瓷泵、蠕动泵等灌装方式；机器设计紧凑合理,外形简洁美观,灌装量调节方便,根据瓶盖的不同，可选择采用挂盖、压盖,扎盖和取盖的上盖方式,在灌装上塞扎盖机系列产品的基础上，进行改良设计，并增加了部分附加功能。广泛应用于制药(各种口服液及糖浆液体)食品,日化,油脂,化工和医药等行业,完全符合国家 GMP 要求。
- ✧ 主要用于对 10~500mL 易拉盖,铝塑盖,马口铁螺纹盖的灌装,上盖,扎盖,灌装速度可根据生产需要定制,能满足 40~200 瓶每分钟产能的个性化定制要求,采用 PLC 触摸屏控制,整机结构简单,外观精美,运行稳定，获得了广大用户的一致好评。

✧ HQ-ZY4C1 Automatic liquid filling-capping machine is our company's traditional series of filling sealing equipment, suitable for all kinds of round, Special shaped bottles filling rotary capping.

✧ Different viscosity fluids can be filled, according to the different materials, metal pump, glass pump, ceramic pump, peristaltic pump and other filling methods can be selected; The machine's design is compact and reasonable, the appearance is simple and beautiful, the filling quantity adjustment is convenient, according to the bottle cap, the upper cap method, hanging cap, pressing cap, grip cap and taking cap can be selected. Widely used in pharmaceutical (All kinds of oral liquid and syrup liquid), Food, daily chemical, oil, chemical and medicine industries, Fully in line with national

GMP requirements;

H&Q=HighQuality Cellphone/WhatsApp: +86-18605120217 exportmanager@hq-autopack.com

☼Mainly used for filling 10~500 mL, aluminum plastic cap, tinplate thread cap, upper cap, tie cap, filling speed can be customized according to production needs, can meet 40~200 bottles per minute capacity personalized customization requirements, using PLC touch screen control/common button control, the whole machine structure is simple, beautiful appearance, stable operation, has been the majority of users praise;

性能特点 Performance characteristics:

- 1.操作简便, 进瓶、灌装、上盖、旋盖和出瓶由机器自动完成。
 - 2.PLC 控制,普通按钮控制(可选), 无瓶不灌装, 不上盖, 计量精准;
 - 3.磁力矩旋盖, 无磨损, 旋盖扭力可调, 不伤瓶和盖。
 - 4.整机按 GMP 要求设计。
 - 5.SUS316 不锈钢泵体计量精准操作简单等优点, 完全符合国家 GMP 要求;
 - 6.设备终身维护, 保修期外维修收取工本费, 终身成本价供应零配件, 终身提供技术支持。
- 1.Easy to operate, automatic feeding, filling, upper cap, rotary cap and out bottles;
 - 2.PLC control,common button control (optional), no bottle, no filling, no capping,accurate measurement;
 - 3.Magnetic torque rotary cap, no wear, adjustable torsion of rotary cap, no damage to bottle and cap;
 - 4.Design according to GMP requirements;
 - 5.SUS316 stainless steel pump(Optional pump:metal pump, glass pump, ceramic pump, peristaltic pump Etc.) body measurement accuracy and simple operation,Fully in line with national GMP requirements;
 - 6.Lifetime maintenance of equipment, pass the time of maintenance ,extra fees for the handle fees,cost price of spare parts, technical support for lifetime;

技术参数 Technical parameter:

| | |
|------------------------|----------------------------|
| 灌装范围 Filling range: | 10-500mL |
| 生产产量 Produce capacity: | 40-200 瓶/分钟 Bottles/minute |
| 灌装精度 Filling accuracy: | ≤±1% |
| 旋盖精度 Capping accuracy: | ≥99% |
| 电源 Power supply: | 220V/380V 50/60Hz 1.5Kw |
| 机器重量 Machine weight: | 500Kg |
| 机器尺寸 Machine size: | 2400×1400×1700mm |

产品不断升级换代,如有改动,敬请谅解!

Note: the company's products are constantly updated,if there are changes,without notice,please understand!