


输出轴局部引出图



Technical drawing of a mechanical part, likely a bracket or support, showing a top view and a side view. The top view is a square plate with a central rectangular cutout and four mounting holes. The side view shows the profile of the plate and a vertical support structure. Dimensions are provided in millimeters.



Top View Dimensions:

- Overall width: $\phi 135h7$
- Overall height: $\phi 135h7$
- Central cutout width: $\phi 32h7$
- Central cutout height: 45
- Mounting hole diameter: $\phi 10f7/k9$
- Mounting hole position: P.C.D. $\phi 155.6$

Side View Dimensions:

- Plate thickness: 15
- Support structure height: 45
- Support structure width: $\phi 32h7$

通比	I	使用寿命	20000h (连续运转寿命减半)
额定输出扭矩 T_n	330Nm	等级值	$\leq 75\text{dB}$
急停扭矩 T_{stop}	2.5倍额定输出扭矩	使用温度	$-10^{\circ}\text{C} \sim +90^{\circ}\text{C}$
额定输入转速 n_R	2500rpm	防护等级	IP65
最大输入转速 n_M	5000rpm	润滑	合成润滑油
扭转刚性	23Nm/arcmin	转动惯量 J_1	$23.5\text{kg} \cdot \text{cm}^2$
许用拉力 F_{20}	4800N	标准行程	$\leq \text{arcmin} - 1\text{arcmin}$
容许侧向力 F_{20s}	2400N	效率 η	$\geq 85\%$

<div>新立盈® </div>										<div>深圳新立盈机电有限公司</div>									
140尺寸图																			
XZT140-4ML 安装图																			
2022-04-16																			
共1页										第01页									
视角																			
比例										1:1									
重量																			
图样标记																			
签字																			
更改文件号																			
处数																			
标记																			
设计										会签									
审核										标准化									
工艺										批准									