

# Dissection Table

## QCT-1800



Application: Hospital pathology department, pathology laboratory

1. The equipment complies with the working environment and personnel protection requirements of the pathology laboratory.

The design of space, noise, wind speed, etc. complies with the relevant requirements of the "China Safety and Environmental Protection Regulations". It is fully functional, safe and non-toxic, and easy to operate.

2. Adopt waterproof and anti-corrosion 1.2mm 304# stainless steel shell, elegant appearance, smooth, reasonable design, anti-corrosion, moisture-proof, sturdy and durable, double-layer plate structure side panel, no welding point on the appearance

3. Excellent exhaust system and efficient air suction device can completely exhaust harmful gases with low noise; long strip shutter type acid and alkali resistant stainless steel exhaust holes, equipped with high-quality PVC anti-corrosion air ducts, and adopts domestic well-known brand Fanshida fan, the fan speed is adjustable

4. The cabinet top is equipped with a fully enclosed fluorescent lighting lamp, which is convenient for use in dim light. In addition, a movable spotlight is configured to meet special needs.

5. Use high-quality brand-name telescopic faucet and external spray system, which is simple and convenient to operate.

6. Equipped with a powerful ultraviolet sterilization device (in compliance with CNS regulations)

7. The operating table is made of 1.5mm 304# stainless steel plate, which is corrosion-resistant, durable and easy to clean. The table is equipped with a special flushing pool and a drain funnel with a filter screen below.

8. The cabinet is equipped with stainless steel hooks for easy access to items.

9. The hot and cold water supply and drainage system uses an international brand instant water heater, which can be used immediately without waiting, and provides unlimited hot water supply.

10. Pipeline crushing system. Imported pipeline crusher is used. The debris after material collection is flushed into the pool with water, and then discharged into the sewer after being crushed, which not only saves the tedious cleaning work, but also does not cause sewer blockage.

11. Dimensions: 1800x750x1950mm

12. The air inlet adopts shutter type, and the upper opening enables the upper fan to absorb air to prevent gas backflow, which is beautiful and practical.

13. The side of the slightly inclined workbench drains water, making it easy to flush the table.

14. The drain nozzle switch is beautiful and durable.

15. 1.5mm thick 304 stainless steel tabletop with reinforced ribs at the bottom, load-bearing and corrosion-resistant.

16. The bottom cabinet is concave, which is convenient for staff to sit and operate or record; the integrated sink is beautiful and has no leakage concerns.

17. The operating table is large and easy to operate.

18. Standard automatic countertop flushing device and retractable faucet for easy countertop flushing.

19. It can be equipped with a grinder, water heater, eye washer, hand dryer, etc. to prevent the sewage pipe from being blocked and facilitate operation in winter.



No.114, Building 15 No.644 Shibe  
Industrial Road, Dashi Street, Panyu  
District, Guangzhou, China



020-31031012



13318866285



gzxiuwei@126.com



www.xwlabware.com  
www.gzxiuwei.cn