

Planetary Lighting (Shenzhen) Group Co., Ltd

LED SCR DIMMING PANEL LIGHT 12W



CE RoHS IP20

Benefits

Excellent lighting effect

- High quality LED and robust aluminium frame to assure good heat dissipation
- Good uniformity with well-designed side-lit technology

High efficiency

- Up to 90 lm/W Efficacy
- Warranty 3 years

Flexibility

- T-bar recessed, suspending, surface mounting installation
- Offer normal and customized panel.

Core materials

- LM-80 certified
- PS LGP
- TUV SAA CE driver

Applications

- Office Banks
- Express Stores
- Hospitals Schools

Planetary Lighting (Shenzhen) Group Co., Ltd

LED SCR DIMMING PANEL LIGHT 12W

Products Data

Item Name:	YZS-PND-TR-12W		
Dimension(mm)	Diameter size 175mm, Hole Size 165mm		
Optical Parameters			
Lumen Flux	960 LM	1100 LM	LED SANAN
Efficacy	80-90 lm/W		
CCT	3000K/4000K/6000K Option		
CRI	>80		
Beam Angle	120°		
Electrical and Mechanical Specifications			
Input Voltage	200-240Vac		
Power Consumption	12W		
Power Factor	>0.9		
Flickering	Flash free		
LGP	PS		
Cover Lens	PS		
Housing	Aluminum 2835 White finished		
System Specifications			
Dimmable	SCR DIMMING		
LED Driver	DAGL		
Installation	T-bar Recessed, Suspended, Surface Mounting		
Operating Tem.	-20° C to +40° C		
Storage Tem.	-20° C to +80° C		
Environment	Indoors use only		
Safety Approval	Electrical Protection Class II CE, RoHS		
Warranty	3 Years Warranty Option		