



# TECHNICAL DATA SHEET

Soft Film Textile

内光软膜布

Code: TX8807S

## Features:

1. **100% PVC free** with PU & PA directly coating.
2. Super **soft** and **smooth** feeling.
3. Suitable for **UV/ECO-SOLVENT** printing, presenting fine images.
4. **“S”** means **“fire retardant”**.

PROPERTIES	METRIC
Weight	140g/sq.m.
Base Fabric	100% Polyester (100g/sq.m.)
Coating	PU & PA Directly (40g/sq.m.)
Thickness	0.20mm
Standard Width	1.6-3.3m
Standard Length	100m
Texture	Woven
Light Transmittance	35±5%
Flame Resistance	German FR-B1/NFPA 701 (SGS)
Eco Certification	EU REACH (SGS)
Heavy Metal Detection	ROHS 2.0 (SGS)
Cold Resistance	-15℃
Yellowing Resistance	Level 4-5
Lifetime	2 Years
Ink	UV/ECO-SOLVENT
Applications	LED Light Boxes, Indoor Advertising, etc.

Zhejiang Chengrudan Coating Material Co., Ltd.

Add: No. 61, Xinmin Road, Warp Knitting Industrial Zone, Maqiao Street, Haining, Jiaxing, Zhejiang, China

Email: [manager@crdcoating.com](mailto:manager@crdcoating.com)

Web: [www.crdcoating.com](http://www.crdcoating.com)