






E534710

Parameter	Symbol	Rating	Units
Short circuit current	I _{sc}	14	uA
Drop-out voltage	V _{oc}	8.3	V
Turn-On Time	T _{on}	0.8	ms
I/O Breakdown Voltage	V _{io}	2500	V _{rms}



1. LED Anode
2. LED Cathode
3. Cathode
4. Anode

(Unit: mm)



Function

1. High-speed switching

Since release time is 0.1 ms, the MOSFET or other load can be turned off quickly in urgent situations.

2. Space saving

With a built-in control circuit, an external resistor is not needed. This contributes to making substrates more compact.

Applications


These advantages make APSEI Photorelays the ideal choice for:

MOSFET driver

Power supply (V_{cc}) for electronic circuits

TPYES

Category	Output Rating		Package	Part No.	Packing Quantity
	Drop-out voltage (Typ.)	Short circuit current (Typ.)			
Driver	8.3V	14uA	SOP-4	APV1124S	2000pcs /reel



Absolute Maximum Ratings (Ta = 25°C)










Item		Symbol	Value	Units	Note
Input	Continuous LED Current	I _F	2~50	mA	
	LED Reverse Voltage	V _R	5	V	
	Peak Forward Current	I _{FP}	1.0	A	
	Power Dissipation	P _O	75	mA	
Output	Maximum Forward Voltage	V	8.0	V _(DC)	I _F =10uA
	Maximum Reverse Current	I _R	10	uA _(DC)	V _R =10V
I/O Isolation Voltage		V _{I/O}	2500	V _{rms}	RH=60%, 1min
Operating Temperature		T _{Opr}	-40 to +85	°C	
Storage Temperature		T _{Stg}	-40 to +125	°C	
Pin Soldering Temperature		T _{Sol}	260	°C	10 sec max.

Electrical Characteristics (Ta = 25°C)

Item		Symbol	MIN.	TYP.	MAX.	Units	Conditions
Input	LED Forward Voltage	V _F		1.2	1.4	V	I _F =10mA
	LED Reverse Current	I _R			10	uA	V _R =5V
	Operation LED Current	I _{Fon}		0.5	5.0	mA	
	Recovery LED Current	I _{Off}	0.2		0.5	mA	
Output (Coupled)	Minimum Open Circuit Voltage	V _O	5.0	8.3		V	I _F =10mA, R _L =10MΩ
	Minimum Short Circuit Current	I _S	5.0	14		uA	I _F =10mA, R _L =100Ω
	Turn-on Time	T _{on}		0.8		ms	I _F =10mA, C _L =1000pF
	Turn-off Time	T _{off}		0.1		ms	
	I/O Capacitance	C _{I/O}		1.0		pF	f=1MHz
	I/O Isolation Resistance	R _{I/O}	10 ¹⁰			Ω	DC500V


Please obey the following conditions to ensure proper device operation and resetting. Input LED current (Recommended value): I_F ≥5mA and ≤30mA

Engineering Data




Dimensions and Package


Marking




Surface mount terminal type




Lable





Recommended mounting pad (Top view)



Tape dimensions




Dimensions of tape reel




Using Methods

Examples of resistance value to control LED forward current ($I_F=5\text{mA}$)



E1	R1 (Approx)
3.3V	300 Ω
5.0V	600 Ω
12V	1.9K Ω
24V	4.1K Ω

LED forward current must be more than 5mA , at $I(\text{MIN})$,and less than 30mA , at $I(\text{MAX})$.




Recommended Operating Conditions

Please obey the following conditions to ensure proper device operation and resetting. Input LED current (Recommended value):


Characteristic	Symbol	Min	Typ.	Max	Unit
Forward current	I_F	5.0	7.0	30	mA

Protection Circuit

Clamp diode is connected in parallel with the load.
Absorb capacity with external diode.



CR Snubber is connected in parallel with the load.
Absorb capacity with buffer capacity.



When adding diodes, buffer circuits (C-R), and other protections, they need to be installed near the MOS RELAY to be effective.
Adding protection elements may result in a slow reset time, so adjust them according to the actual situation before use.

Note: When developing designs using this product, perform the expected performance of the equipment under the operating conditions recommended by the guidelines in this document. Continuous use under heavy loads (including, but not limited to, the application of high temperatures/current/voltage and significant changes in temperature, etc.) may result in deterioration of the reliability of this product.



RESTRICTIONS ON PRODUCT USE

APSEMI Co. and its subsidiaries and affiliates (collectively "APSEMI") reserve the right to make changes to all information contained in this document relating to hardware, software, and systems (collectively "Products").

No information in this document may be reproduced without the prior written permission of APSEMI. Even with APSEMI's written permission, this document may only be reproduced if it is guaranteed to be unaltered or missing.

APSEMI assumes no responsibility for unintended uses of the product:

Unintended uses include, but are not limited to, equipment used in nuclear facilities, equipment used in the aerospace industry, medical equipment, automobiles, trains, ships, and other transportation equipment, traffic signaling equipment, equipment used for the control of combustion or explosions, safety devices, elevators and escalators, equipment used in electrical power-related applications, and equipment used in financial-related applications.

APSEMI assumes no responsibility for the product if you use it for any purpose other than the specific purpose described in this document.

- The information contained herein is provided only as a guide for the use of the product. APSEMI assumes no responsibility for infringement of third party patents or any other intellectual property rights that may result from the use of the product. This document does not grant any license, express or implied, estoppel or otherwise, to any intellectual property.

- GaAs (Gallium Arsenide) is used in products and is harmful to humans. Inadvertent ingestion or absorption of GaAs can harm the human body, so handle the product with care and do not break, cut, crush, grind, chemically dissolve, or otherwise expose GaAs in the product.

- Please be aware of environmental issues and use products in compliance with all applicable laws and regulations governing the inclusion or use of controlled substances, including but not limited to the EU RoHS Directive. APSEMI assumes no responsibility for damages or losses resulting from non-compliance with applicable laws and regulations.